

ALUMINUM CEILING TILES

CLIP-IN (Plain / Perforated)

TECHNICAL DATA SHEET



Features and Benefits:



High-quality properties of non-combustibility and mechanical stability.



Fire & moisture resistance, corrosive resistance & light reflection.



Easy to clean, durable, easy to install.



Available as perforated for acoustical usage.



Available in Anti-Bacteria



Environmentally friendly and recyclable.



Product Specifications

Material	Aluminum alloy 3005, 3105, 1100, comply with BS 476 PART 7-1987 ,ASTM B 209, ASTM D 2247, ASTM E 1477-98 and EN 1396.				
Available Thickness	0.4	0.5	0.6	0.7	up to 1.0 mm
	other thickness available upon request				
Colours	Available in 5 standard colors & can be produced up to 110 different colors depending on quantity & client request.				
Finish	pre-painted polyester coating (primer +polyester) thk=25 microns from front & (polyester)5 microns from the back According to EN 1396. Available also in polyester powder coating finish with thk=60-80 microns & also available in Anti-Bacterial paint.				
Suspension System	(Concealed) (Clip-In Suspension system Clip-In advanced Suspension system).				
Texture	Available in plain, or with full perforation(standard) for acoustical usage(Circular perforation Ø 1.8mm) with acoustical black tissue from the backside, Also customized sizes of perforation & designs are available upon client request.				
Fire rating (Raw Material)	Fire Rated Class 0 as per british standard BS 476 PART 7-1987. Surface Flame Spread test Class 0 as per british standard BS 476 PART 6 & 7.				
Humidity Resistance (Raw Material)	Humidity resistance According to ASTM D 2247.				
Light reflectance (Raw Material)	Light Reflectance more than 0.75 According to ASTM E 1477-98.				
Water Vapour transmission (Raw Material)	Water Vapour transmission (NIL).				
Sizes	600*600/1200mm (Plain / perforated), 300*300/1200mm (Plain / perforated). Customized sizes in length & width from 30 cm up to 3m(Plain / perforated) upon request.				

Applications


Wide range for usage/application area (bathrooms, kitchens, wet areas, hospitals, shops, offices, airports & exhibition centers, halls, computer rooms & utility rooms...etc).



System Contents (Components)


CLIP-IN SUSPENSION SYSTEM (Standard)

1. Aluminum clip-in ceiling tiles .
2. Spring tee.
3. Spring tee bracket & spring tee joiner.
4. U-shape wall angle .
5. Suspension accessories (rod hangers, adjustment clips & anchor bolts).



CLIP-IN SUSPENSION SYSTEM (Advanced)

1. Aluminum clip-in ceiling tiles .
2. Spring tee and spring tee joiner.
3. C-Channel.
4. U-Shape Wall angle
5. Suspension Accessories (Omega Clip, C-channel Clip, Threaded Rod, Nut, Drop Anchor).



Supplier and Manufacturer: JAWDAH INDUSTRIAL COMPANY LTD.

Country of Origin: Kingdom of Saudi Arabia



JAWDAH

شركة جودة الصناعة المحدودة
Jawdah Industrial Co. Ltd.

Meed Building, Dabab Street, Riyadh, KSA
T: +966 11 216 6616 F: +966 11 216 6606
E: jawdah@jawdah.sa | www.jawdah.sa