

PVC (POLYVINYL CHLORIDE) FILMS

TECHNICAL DATA SHEET



239-573



244-574



251

Features and Benefits:



- Moderate Melt Viscosity
- Easy processing even in injection molding)
- Low content of fines



- Narrow particles size distribution
- High tensile properties



Moisture resistance



Easy to clean



Durable, easy to install.



Environmentally friendly and recyclable.

Applications

- Gypsum tiles Lamination
- Industrial applications
- Rigid sheets and films/decorated applications



Product Specifications

Material	PVC (Polyvinyl Chloride) Films
Roll Width	1.23 Meter
Roll Length	±500 L.M per Roll.
Film Thickness	± 65 microns
Types / Designs	9 different designs
GSM	100 GR/M
Surface	High Quality Finishing
Processing	Gluing, Wrapping, Cold Laminating, Hot Laminating.
Resin K Value	59-60 / TEST METHOD DIN 53726

Supplier and Manufacturer: JAWDAH INDUSTRIAL COMPANY LTD.

Country of Origin: Kingdom of Saudi Arabia



JAWDAH

شركة جودة الصناعة المحدودة
Jawdah Industrial Co. Ltd.

Meed Building, Dabab Street, Riyadh, KSA

T: +966 11 216 6616 F: +966 11 216 6606

E: jawdah@jawdah.sa | www.jawdah.sa

PVC FILMS (Designs & Colors)



154



155



251



567



572 WHITE



573




574




575



991



996




572-1 GOLD




238-5 SILVER



169-13



573-1 GOLD



81220-2



81602-7



910702-13A